



Ceramic Plus

For PU coated ceramic, anodized aluminum, leather, some plastics, wood, paper, vinyl-covered magnets, coated metal & more

OUR PAPER FUNCTIONS IN MOST COLOR LASER COPIERS AND COLOR PRINTERS, WITH AND WITHOUT THE USE OF FUSER OIL

PRINTING:

- Use Multi-Function Tray. The image side is placed face up in the tray.
- 8.5" x 11" sheets feed long edge. 11" x 17" sheets feed short edge.
- Fan sheets prior to loading.
- Use Mirror Image setting so image will read correctly after application.
- Use Transparency, Label, Heavy Paper Mode Setting.
- Set machine as you normally would for the type of original used (Le, PHOTO, TEXT, etc.).

MUG/CERAMIC TILE (COATED):

- Run copies as above.
- Cut out image and tape onto mug using heat resistant tape.
- Place into mug press at 310°F for 180 seconds and adjust moderate pressure. Make sure image is straight and not closer than 1" from each side of handle. Also image area should not be closer than 3/8" from top or bottom of mug.
- Carefully remove transfer paper from mug in one easy stroke.
CAUTION HOT!!! Do not touch imaged area!!!
- Now place mug into curing unit for 90 seconds, remove.
CAUTION, HOT!!!
- Cool in running water or set aside and allow cooling.

ALUMINUM LICENSE PLATES:

- Run copies as above.
- Attach silicone pad to top of heat press.
- Cut transfer and place on license plate.
- Press at 275°F, medium pressure for 180 seconds.
CAUTION, HOT!!!
- Allow cooling and carefully remove transfer paper.
- If you desire a high-gloss finish, take an unused piece of Ceramic Plus paper and press again for 40 seconds.
- Allow cooling and carefully remove paper.

MAGNET TRANSFER:

- Run copies as above.
- Attach silicone pad to top of heat press.
- Cut and place transfer paper on white vinyl side of magnet.
- Press at 275°F, medium pressure for 120 seconds.
- Allow cooling completely and carefully remove transfer paper.
- If you desire a high-gloss finish, take an unused portion of the Ceramic Plus paper and press again for 40 seconds.
- Allow cooling and carefully remove paper.

LEATHER TRANSFER:

- Run copies as above.
- Cut transfer and place on leather.
- Press at 275° degrees, medium pressure for 100 seconds.
- Allow cooling completely.
- Carefully remove transfer paper.

PAPER PRODUCTS:

- Run copies as above.
- Attach silicone pad to top of heat press.
- Cut and place transfer on white paper.
- Press at 275°F, medium pressure for 45 seconds.
- Carefully remove transfer paper.
CAUTION, HOT!!!
- Allow cooling.

WOOD PRODUCTS:

- Run copies as above.
- Attach silicone pad to top of machine.
- Cut transfer and place on wood.
- Press at 275°F, medium pressure for 90 seconds.
- Carefully remove transfer paper.
CAUTION, HOT!!!
- Allow cooling.

IMPORTANT: Please keep your 1 Step® Ceramic Plus paper in the plastic bag until actual use. This will prevent moisture from forming. Close the bag after each use.